


SIZE	ØNB	L	ØD	Øf	B	'C'	ØG	'H'
1"	25	127	108	50.8	11.2	79.3	16	4
1½"	38	165	127	73	14.3	98.5	16	4
2"	50	203	152.4	92	16	120.6	19	4
2½"	64	216	178	105	17.5	139.7	19	4
3"	76	241	190.5	127	19	152.4	19	4
4"	100	292	228.6	157.2	24	190.5	22.4	8
6"	150	406	279.4	216	25.4	241.3	22.4	8
8"	200	495	343	270	28.5	298.5	22.4	8
10"	250	622	406.4	324	30.2	362	25.4	12
12"	300	698	482.6	381	31.8	431.8	25.4	12
14"	337	787	533.4	413	35	476.3	28.6	12

SR. NO.	PARTS NAME	MATERIAL
1	BODY	ASTM A 216 Gr. WCB
2	COVER	ASTM A 216 Gr. WCB
3	SCREEN	SS 304
4	GASKET	SS 304 SPIRAL WOUND WITH GRAPHOLITE FILLER
5	BOLT & NUT	ASTM A 193 Gr. B7 / A193 Gr. 2H

TECHNICAL DATA	
DESIGN & MANUFACTURING STD.:	ASME B16.34
END CONNECTIONS :	FLANGED AS PER ASME B 16.5 - 150#

HYD. TEST PRESSURE	
BODY	32 KG/CM2

DRN. : B.M.P	 NORFLOW CONTROLS Industrial Valves
CHK. : V.G.P	
APRD. : S.K.P	
DATE: 01.04.19	
SCALE: NTS	'Y' STRAINER FLANGED ENDS
DRG NO. : NC/STR/DP/150/40 - 200	